

Call Toll Free 1.866.410.CCTV (2288)
<http://www.cctvstar.com>



1/3" SONY Super HAD CCD II, 3.5~16mm Auto Iris Lens 700 TV Lines (Color), 54 IR LEDs, OSD, IR Control, True Day & Night, 3D-DNR, SENSE UP, BLC, D-WDR, HLM, SMART IR, D-ZOOM, Dual Voltage

Made in Korea

FEATURES

1/3" SONY Super HAD CCD II, 3.5~16mm AVF Lens
700 TV Lines (Color), 54 IR LEDs
OSD, IR Control, True Day & Night
3D-DNR, SENSE UP, BLC, D-WDR, HLM,
SMART IR, D-ZOOM, Dual Voltage

SPECIFICATIONS

Image Sensor	1/3" SONY Super HAD CCD II
Effective Pixel	976(H)X494(V)
Resolution	700 TV Lines (Color)
Sync. Type	Internal
Scanning System	2:1 Interlace
Video Output	1.0 Vp-p (Sync. Negative) Termination 75
Gamma Characteristic	r = 0.45 Typ.
Min. Illumination	0.00001 Lux (F/1.2 Sense-up X256)
S/N Ratio	52 dB or More (AGC Off)
Gain Control	OFF / LOW / MIDDLE / HIGH
Day & Night	Auto / Color / BW / EXT
OSD	Available
IR Smart	ON / OFF Selectable (0~100)
D-WDR	OFF / Low level(0~15) / High Level(0~15)
Backlight	OFF / LOW / MIDDLE / HIGH
Test Illuminance Area	Average test illumination by front view
Power Supply	12V DC / AC 24V
Consumption Current	130mA (IR ON 700mA)
Operating Temp.	14 F to 122 F
Preservation Temp.	- 4 F to 140 F
LED	IR LED 54
Lens	3.5~16mm Auto Iris Varifocal Lens
Dimension	88(W)x 87 (H) x 177(D)mm
Weight Approx.	1320 g.

